

# Bottled Water

## Features

- High quality, high output refrigeration and heating systems
- Same internal components as the Reflections® family
- Solid, one-piece cabinet made from High Density Polyethylene is extremely durable and easy to clean
- No external base plate
- Energy Star rated 2.0L hot tank with On/Off switch
- Stainless steel cold reservoir
- Removable, two-piece, dishwasher safe drip tray
- Includes our dependable No Leak® EZ-Fill® spill guard system
- Available in black or white
- UL certified



IB 210

IW 210

## Models

H&C: IB210, IW210

C&C: IB110, IW110

# Inspirations®

## Power

Voltage (V)	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.44A / 118W / 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (KWH/24hrs)	1.14
% lower than ES Standard	5.0%

## Hot Water System

Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On)	166.57°F / 191.43°F
Hot water ARI Rating	45 6oz > 165°F +/- 10%
Hot Thermostat / Heat Limiter	203°F +/-5.5°F
Hot Thermostat / Thermister Cycle	167°F +/-11°F / 187°F +/-4°F
i-Boil Set Point	N/A
Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On)	N/A
Hot Water Flow Rate	0.96 oz/sec
Hot Water Flow Rate (oz per sec)w/Accu-Temp delay	N/A
Hot Tank Size (L)	2.0L
Heat Band Wattage	450W

## Cold Water System

Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON)	45.87°F / 42.2°F
Cold Water ARI Rating	27 5oz < 50°F +/-10%
Cold Thermostat Set Point	45°F +3°/-8°F
Cold Water Flow Rate	1.4 oz/sec
Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay	N/A
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal.)	1 / 0.55 / 0.4 G

## Weights and Measurements

Net Weight (H&C / C&C Lbs.)	34.6 / 31.68
Gross Weight (H&C / C&C Lbs.)	37.9 / 34.98
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.4x13.5x39 / 13x13.9x40
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL